

|  |   |
|--|---|
| <b>Construction Material (Bathrooms)</b> | Stainless Steel 304                       |
| <b>Flow Rate (L/Min)</b>                 | 9 L/min                                   |
| <b>Hose Supplied</b>                     | 1.5m shower hose                          |
| <b>Manufacturer Guarantee</b>            | 5 Year Manufacturer's Guarantee(Internal) |
| <b>Max. Working Pressure</b>             | 5 bar                                     |
| <b>Maximum Bar Pressure</b>              | 5 bar                                     |
| <b>Minimum Bar Pressure</b>              | 0.2 bar                                   |
| <b>Model Name</b>                        | Thermostatic 2-Way Shower                 |
| <b>Model No</b>                          | RO-H12052TM                               |
| <b>Mount Type</b>                        | Deck Mounted                              |
| <b>Pack Size</b>                         | 1   |
| <b>Parent Colour</b>                     | Brushed Ti-gold/ Matte black              |
| <b>Pieces in Pack/Case</b>               | 1   |
| <b>Pressure Suitability</b>              | Suitable for All Pressure Systems         |
| <b>Product Type</b>                      | Thermostatic 2-Way Shower                 |
| <b>Smart Compatibility</b>               | Not Smart                                 |
| <b>Spout Flow Type</b>                   | Standard                                  |
| <b>Tap Control Type</b>                  | Single Control                            |
| <b>Tap Design</b>                        | Modern                                    |
| <b>Tap Handle Type (Bathrooms)</b>       | Lever                                     |
| <b>Tap Product Type (Bathrooms)</b>      | Thermostatic 2-Way Shower                 |
| <b>Tap Suitability Type (Bathrooms)</b>  | Shower                                    |